(12) **United States Patent**

Presley-Mays

(10) **Patent No.:** **US 6,520,513 B2**

(45) **Date of Patent:** **Feb. 18, 2003**

(54) **GARDEN CART**

(76) Inventor: **Martha Presley-Mays,** Homestead Station 1610 - S. El Dorado St., Stockton, CA (US) 95206

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/897,271**

(22) Filed: **Jul. 3, 2001**

(65) **Prior Publication Data**

US 2003/0006571 A1 Jan. 9, 2003

(51) **Int. Cl.**[7] **B62B 3/02**; B62B 3/10; B62B 11/00

(52) **U.S. Cl.** **280/32.5**; 280/47.19; 280/47.371; 280/47.24; 280/47.35; 280/79.2; 280/79.11; 280/659

(58) **Field of Search** 280/47.34, 47.35, 280/47.371, 79.11, 79.2, 47.19, 47.24, 32.5, 653, 655.1, 659; 220/783, 797, 253, 500

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,318,315 A	*	6/1994	White et al.	....	280/47.18
5,474,483 A	*	12/1995	Sun	....	280/33.998
D365,905 S	*	1/1996	Yemini	....	D34/19
5,833,250 A	*	11/1998	Schier et al.	....	280/47.19
5,876,047 A	*	3/1999	Dennis	....	280/47.35
6,079,720 A	*	6/2000	Spear et al.	....	280/33.998
6,176,559 B1	*	1/2001	Tiramani et al.	....	280/47.19
6,260,865 B1	*	7/2001	Yacobi et al.	....	248/346.01
6,264,216 B1	*	7/2001	Wilson	....	280/30

* cited by examiner

Primary Examiner—Brian L. Johnson
Assistant Examiner—Brian L Swenson

(57) **ABSTRACT**

Garden cart with a hollow cart housing comprised of a lower half and an upper half, the top half and bottom half removably joined by a channel located around the perimeter of the lower half, the lower half having a plurality of wheels attached for the purpose of rolling, a rotatable pull handle attached to the front lower surface of the lower cart half, a removable, replaceable tool box that inserts into the top cart half, a hinged and padded seat located on the upper front of said top cart half, a lower tool handle holding receptacle portion located on the lower rear portion of said lower cart half, a plurality of spring biased holding fingers for holding tools located on the rear and side surface of said upper cart half, and said top half capable of being easily removed from said bottom half so that said bottom cart half can be used as a conventional wheel barrow.

2 Claims, 9 Drawing Sheets